



METAL STAINLESS STEEL

TUBERÍA
INOXIDABLE:
REDONDOS

Índice

1 - Redondo Milimétrico

2 - Redondo ISO

3 - Redondo Schedule

CALIDADES: AISI-304 Y AISI-316.

TUBO NORMA: DIN-17455/17457- EN 10217-7 – EN 10296-2

1 - REDONDO MILIMÉTRICO

DIAMETRO EXT. (mm)	ESPESOR (mm)	PESO APROX KG/MT
6,0	1,0	0,126
8,0	1,0	0,176
10,0	1,0	0,227
12,0	1,0	0,277
13,0	1,0	0,320
15,0	1,5	0,510
16,0	1,0	0,378
18,0	1,0	0,426
18,0	1,5	0,623
19,0	1,5	0,661
20,0	1,0	0,478
20,0	1,5	0,699
23,0	1,5	0,812
25,0	1,0	0,604
25,0	1,5	0,888
28,0	1,5	1,001
30,0	1,5	1,077
31,7	1,3	0,959
33,0	1,5	1,190
35,0	1,5	1,266
38,0	1,5	1,379
40,0	1,5	1,480
43,0	1,5	1,568
44,0	2,0	2,116
50,8	1,5	1,863
53,0	1,5	1,946
63,5	1,5	2,343
73,0	1,5	2,706
76,0	1,5	2,816
84,0	2,0	4,132
104,0	2,0	5,140
129,0	2,0	6,400
154,0	2,0	7,666
254,0	2,0	10,180
304,0	2,0	15,220
354,0	2,0	17,741

2 - REDONDO ISO

PULGADAS	DN	MEDIDAS (mm)	PESO (Kg/m)
3/8"	DN-10	17,2 X 1,6	0,646
3/8"	DN-10	17,2 X 2	0,766
1/2 "	DN-15	21,3 X 1,6	0,817
1/2 "	DN-15	21,3 X 2	0,973
1/2 "	DN-15	21,3 X 2,6	1,285
3/4 "	DN-20	26,9 X 1,6	1,049
3/4 "	DN-20	26,9 X 2	1,255
3/4 "	DN-20	26,9 X 2,6	1,600
1 "	DN-25	33,7 X 1,6	1,332
1 "	DN-25	33,7 X 2	1,598
1 "	DN-25	33,7 X 2,6	2,050
1-1/4 "	DN-32	42,4 X 1,6	1,694
1-1/4 "	DN-32	42,4 X 2	2,036
1-1/4 "	DN-32	42,4 X 2,6	2,600
1-1/4 "	DN-32	42,4 X 3	2,979
1-1/2 "	DN-40	48,3 X 1,6	1,939
1-1/2 "	DN-40	48,3 X 2	2,333
1-1/2 "	DN-40	48,3 X 2,6	3,040
1-1/2 "	DN-40	48,3 X 3	3,424
2 "	DN-50	60,3 X 1,6	2,438
2 "	DN-50	60,3 X 2	2,938
2 "	DN-50	60,3 X 2,6	3,770
2 "	DN-50	60,3 X 3	4,331
2-1/2 "	DN-65	76,1 X 1,6	3,095
2-1/2 "	DN-65	76,1 X 2	3,734
2-1/2 "	DN-65	76,1 X 2,6	4,820
2-1/2 "	DN-65	76,1 X 3	5,526
3 "	DN-80	88,9 X 1,6	3,627
3 "	DN-80	88,9 X 2	4,379
3 "	DN-80	88,9 X 2,6	5,650
3 "	DN-80	88,9 X 3	6,494
3-1/2 "	DN-90	101,6 X 2	5,019
3-1/2 "	DN-90	101,6 X 2,6	6,492
3-1/2 "	DN-90	101,6 X 3	7,454

2 - REDONDO ISO

PULGADAS	DN	MEDIDAS (mm)	PESO (Kg/m)
4 "	DN-100	114,3 X 1,6	4,683
4 "	DN-100	114,3 X 2	5,659
4 "	DN-100	114,3 X 2,6	7,324
4 "	DN-100	114,3 X 3	7,730
5 "	DN-125	139,7 X 2	6,940
5 "	DN-125	139,7 X 2,6	8,980
5 "	DN-125	139,7 X 3	10,334
6 "	DN-150	168,3 X 2	8,381
6 "	DN-150	168,3 X 2,6	10,860
6 "	DN-150	168,3 X 3	12,496
8 "	DN-200	219,1 X 2	10,936
8 "	DN-200	219,1 X 2,6	14,180
8 "	DN-200	219,1 X 3	16,329
10 "	DN-250	273,1 X 2	13,658
10 "	DN-250	273,1 X 2,6	17,722
10 "	DN-250	273,1 X 3	20,412
12 "	DN-300	323,9 X 2	16,223
12 "	DN-300	323,9 X 2,6	21,057
12 "	DN-300	323,9 X 3	24,260

3 - REDONDO SCHEDULE

Diámetro Nominal (pulgadas)	Diámetro Exterior (mm)	Espesor pared y peso por metro					
		SCHEDULE 10 S		SCHEDULE 40 S		SCHEDULE 80 S	
		Esp:mm	Kg/m	Esp:mm	Kg/m	Esp:mm	Kg/m
1/4 "	13,71	1,65	0,50	2,24	0,64	3,02	0,81
3/8 "	17,15	1,65	0,64	2,31	0,86	3,20	1,12
1/2 "	21,34	2,11	1,02	2,77	1,29	3,73	1,64
3/4 "	26,67	2,11	1,30	2,87	1,71	3,91	2,23
1 "	33,40	2,77	2,12	3,38	2,54	4,55	3,29
1-1/4 "	42,16	2,77	2,73	3,56	3,44	4,85	4,53
1-1/2 "	48,26	2,77	3,15	3,68	4,11	5,08	5,49
2 "	60,33	2,77	3,99	3,91	5,52	5,54	7,60
2-1/2 "	73,03	3,05	5,34	5,16	8,77	7,01	11,59
3"	88,90	3,05	6,56	5,49	11,45	7,62	15,51
4"	114,30	3,05	8,50	6,02	16,32	8,56	22,62
6"	168,28	3,40	14,04	7,11	28,69	10,97	43,16
8 "	219,08	3,76	20,24	8,18	43,13	12,70	64,54
10 "	273,05	4,20	28,17	9,27	60,31	12,70	81,55
12 "	323,85	4,57	36,51	9,53	73,88	12,70	97,46